

Air Conditioning

Product Information

PKA-RP Power Inverter Heat Pump Wall Mounted System

Making a
World of
Difference



PKA-RP Power Inverter Heat Pump Wall Mounted System

Our wide range of power inverters offer customers high seasonal efficiency, advanced control options and quiet operation, whilst providing greater flexibility and ease of installation.

Key Features

- Swing Vane Mode with Auto Vane Shutter
- Infra-red remote controller
- Auto-Restart
- Quiet operation
- Auto-Changeover
- Hot Start - draught prevention
- Factory charged refrigerant up to 30m
- Standard filter
- Quick clean design
- Replace Technology available
- Refrigerant volume check function
- Duty Standby Operation
- Demand Control
- Noise Reduction
- Optional Heating Only



Air Conditioning | Heating
Ventilation | Controls

Air Conditioning

Product Information

PKA-RP Power Inverter Heat Pump Wall Mounted System

Making a
World of
Difference



PKA-RP - INDOOR UNITS		PKA-RP35HAL	PKA-RP50HAL	PKA-RP60KAL	PKA-RP71KAL	PKA-RP100KAL	PKA-RP100KAL
CAPACITY (kW)	Heating (nominal)	4.1 (1.6-5.2)	5.0 (2.5-7.3)	7.0 (2.8-8.2)	8.0 (3.5-10.2)	11.2 (4.5-14.0)	11.2 (4.5-14.0)
	Cooling (nominal)	3.6 (1.6-4.5)	4.6 (2.3-5.6)	6.1 (2.7-6.7)	7.1 (3.3-8.1)	10.0 (4.9-11.4)	10.0 (4.9-11.4)
	Heating (UK)	3.5 (1.35-4.4)	4.25 (2.15-6.2)	5.95 (2.4-6.95)	6.8 (3.0-8.65)	9.5 (3.85-11.9)	9.5 (3.85-11.9)
	Cooling (UK)	3.3 (1.45-4.15)	4.23 (2.1-5.15)	5.5 (2.5-6.15)	6.55 (3.05-7.45)	9.2 (4.5-10.5)	9.2 (4.5-10.5)
SHF (nominal & UK)		0.81	0.72	0.86	0.78	0.73	0.73
COP / EER (nominal)		3.83 / 3.83	3.33 / 3.26	3.57 / 3.81	3.65 / 3.94	3.68 / 3.77	3.68 / 3.77
SCOP / SEER (BS EN14825)		3.9 / 5.7	4.0 / 5.3	4.2 / 6.3	4.3 / 6.5	4.0 / 6.1	4.0 / 6.0
ErP ENERGY EFFICIENCY CLASS Heating/Cooling		A / A+	A+ / A	A+ / A++	A+ / A++	A+ / A++	A+ / A++
AIRFLOW (m³/min) Lo-Mi-Hi		9-10.5-12	9-10.5-12	18-20-22	18-20-22	20-23-26	20-23-26
PIPE SIZE mm (in)	Gas	12.7 (1/2")	12.7 (1/2")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")
	Liquid	6.35 (1/4")	6.35 (1/4")	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")
SOUND PRESSURE LEVEL (dBA)		36-40-43	36-40-43	39-42-45	39-42-45	41-45-49	41-45-49
SOUND POWER LEVEL (dBA)		60	60	64	64	65	65
DIMENSIONS (mm) Width x Depth x Height		898 x 249 x 295	898 x 249 x 295	1170 x 295 x 365	1170 x 295 x 365	1170 x 295 x 365	1170 x 295 x 365
WEIGHT (kg)		13	13	21	21	21	21
ELECTRICAL SUPPLY		Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit
FUSE RATING (BS88) - HRC (A)		6	6	6	6	6	6
INTERCONNECTING CABLE No. Cores		4	4	4	4	4	4

PUHZ-ZRP - OUTDOOR UNITS		PUHZ-ZRP35VKA	PUHZ-ZRP50VKA	PUHZ-ZRP60VHA	PUHZ-ZRP71VHA	PUHZ-ZRP100VKA	PUHZ-ZRP100YKA ③ Three Phase
SOUND PRESSURE LEVEL (dBA) Heating/Cooling		46 / 44	46 / 44	48 / 47	48 / 47	51 / 49	51 / 49
SOUND POWER LEVEL (dBA) Cooling		65	65	67	67	69	69
WEIGHT (kg)		43	46	67	67	116	124
DIMENSIONS (mm) Width x Depth x Height		809 x 300 x 630	809 x 300 x 630	950 x 330 + 30 x 943	950 x 330 + 30 x 943	1050 x 330 + 30 x 1338	1050 x 330 + 30 x 1338
ELECTRICAL SUPPLY		220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	380-415v, 50Hz
PHASE		Single	Single	Single	Single	Single	Three
SYSTEM POWER	Heating/Cooling (nominal)	1.07 / 0.94	1.50 / 1.41	1.96 / 1.60	2.19 / 1.80	3.04 / 2.65	3.04 / 2.65
	Heating/Cooling (UK)	0.84 / 0.91	1.25 / 1.28	1.42 / 1.67	1.60 / 1.86	2.36 / 2.58	2.36 / 2.58
STARTING CURRENT (A)		4.0	5.0	5.0	6.0	12.0	4.0
SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX]		4.22 / 3.94 [13.4]	7.16 / 6.59 [13.4]	9.23 / 8.11 [19.4]	8.75 / 7.79 [19.4]	11.46 / 11.44 [27.1]	4.82 / 4.41 [8.6]
FUSE RATING (BS88) - HRC (A)		16	16	25	25	32	16
MAINS CABLE No. Cores		3	3	3	3	3	5
MAX PIPE LENGTH (m)		50	50	50	50	75	75
MAX HEIGHT DIFFERENCE (m)		30	30	30	30	30	30
CHARGE R410A (kg) - 30m		2.2	2.4	3.5	3.5	5.0	5.0

③ Three Phase



Telephone: 01707 282880

email: airconditioning@meuk.mee.com web: www.airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division
Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881

IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland
Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

Country of origin: United Kingdom - Japan - Thailand - Malaysia. ©Mitsubishi Electric Europe 2013. Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registered trademarks of their respective owners.



Effective as of February 2013



www.greengateway.mitsubishielectric.co.uk

Mitsubishi Electric's commitment
to the environment



Follow us @green_gateway



Connect with Green Gateway



[mitsubishielectric2](https://www.youtube.com/mitsubishielectric2)