



PLA-ZRP Power Inverter Heat Pump

4-Way Blow Ceiling Cassette System (Single Phase)

Our wide range of Power Inverters offer customers high seasonal efficiency, advanced control options and quiet operation, whilst providing greater flexibility and ease of installation.



Air Conditioning | Heating
Ventilation | Controls

Key Features

- Swing Vane Mode with Auto Vane Shutter
- Auto-Restart
- Quiet operation
- 72 different airflow patterns - 2, 3 or 4 way discharge
- High ceiling compatibility through wide flow air outlets
- Auto-Changeover
- Hot Start - draught prevention
- Factory charged refrigerant up to 30m
- Long-life filter with optional high efficiency filter also available
- Drain lift pump as standard
- Fresh air knockout
- Ceiling soiling prevention
- Replace Technology available
- Refrigerant volume check function
- Optional I-See Sensor
- Duty Standby Operation
- Optional Demand Control
- Optional Noise Reduction
- Optional Heating Only

Air Conditioning

Product Information

PLA-ZRP Power Inverter Heat Pump 4-Way Blow Ceiling Cassette System (Single Phase)

Making a
World of
Difference



PLA-ZRP - INDOOR UNITS		PLA-ZRP35BA	PLA-ZRP50BA	PLA-ZRP60BA	PLA-ZRP71BA	PLA-ZRP100BA	PLA-ZRP125BA2	PLA-ZRP140BA
CAPACITY (kW)	Heating (nominal)	4.1 (1.6-5.2)	6.0 (2.5-7.3)	7.0 (2.8-8.2)	8.0 (3.5-10.2)	11.2 (4.5-14.0)	14.0 (6.0-16.0)	16.0 (5.7-18.0)
	Cooling (nominal)	3.6 (1.6-4.5)	5.0 (2.3-5.6)	6.1 (2.7-6.5)	7.1 (3.3-8.1)	10.0 (4.9-11.4)	12.5 (5.5-14.0)	13.4 (6.2-15.0)
	Heating (UK)	3.5 (1.35-4.4)	5.1 (2.15-6.2)	6.0 (2.38-6.97)	6.8 (3.0-8.65)	9.5 (3.85-11.9)	11.9 (4.25-13.6)	13.6 (4.85-15.3)
	Cooling (UK)	3.3 (1.45-4.15)	4.6 (2.1-5.15)	5.6 (2.48-5.98)	6.55 (3.05-7.45)	9.2 (4.5-10.5)	11.5 (5.05-12.9)	12.9 (5.7-14.1)
SHF (nominal & UK)		0.96	0.84	0.77	0.85	0.74	0.74	0.72
COP / EER (nominal)		4.77 / 4.56	3.82 / 3.50	3.43 / 3.43	4.02 / 4.01	4.29 / 3.85	3.81 / 3.23	3.40 / 3.07
SCOP / SEER (BSEN14825)		4.6 / 6.8	4.6 / 6.4	4.2 / 6.1	4.5 / 6.7	4.6 / 6.5	4.1 / 6.0	4.5 / 6.1
ErP ENERGY EFFICIENCY CLASS	Heating/Cooling	A++ / A++	A++ / A+	A+ / A++	A+ / A++	A++ / A++	N/A	N/A
AIRFLOW (m³/min)	Lo-Mi-Mi2-Hi	11-13-15-16	12-14-16-18	12-14-16-18	17-19-21-23	20-23-26-30	22-25-28-31	24-26-29-32
PIPE SIZE mm (in)	Gas/Liquid	12.7 (1/2") / 6.35 (1/4")	12.7 (1/2") / 6.35 (1/4")	15.88 (5/8") / 9.52 (3/8")	15.88 (5/8") / 9.52 (3/8")	15.88 (5/8") / 9.52 (3/8")	15.88 (5/8") / 9.52 (3/8")	15.88 (5/8") / 9.52 (3/8")
SOUND PRESSURE LEVEL (dBA)	Lo-Mi-Mi2-Hi	27-28-29-31	28-29-31-32	28-29-31-32	28-30-32-34	32-34-37-40	34-36-39-41	36-39-42-44
SOUND POWER LEVEL (dBA)		54	55	55	58	65	66	70
DIMENSIONS (mm)	Width x Depth x Height (Grille)	840 (950) x 840 (950) x 258 (35)	840 (950) x 840 (950) x 258 (35)	840 (950) x 840 (950) x 258 (35)	840 (950) x 840 (950) x 298 (35)	840 (950) x 840 (950) x 298 (35)	840 (950) x 840 (950) x 298 (35)	840 (950) x 840 (950) x 298 (35)
WEIGHT (kg)	Unit / Panel	23 / 6	23 / 6	23 / 6	25 / 6	26 / 6	27 / 6	27 / 6
ELECTRICAL SUPPLY		Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit
FUSE RATING (BS88) - HRC (A)		6	6	6	6	6	6	6
INTERCONNECTING CABLE No. Cores		4	4	4	4	4	4	4
GRILLE REFERENCE		PLP-6BA	PLP-6BA	PLP-6BA	PLP-6BA	PLP-6BA	PLP-6BA	PLP-6BA
WIRED REMOTE CONTROLLER REFERENCE		PAR-31MAA	PAR-31MAA	PAR-31MAA	PAR-31MAA	PAR-31MAA	PAR-31MAA	PAR-31MAA

PUHZ-ZRP - OUTDOOR UNITS		PUHZ-ZRP35VKA	PUHZ-ZRP50VKA	PUHZ-ZRP60VHA	PUHZ-ZRP71VHA	PUHZ-ZRP100VKA	PUHZ-ZRP125VKA	PUHZ-ZRP140VKA
SOUND PRESSURE LEVEL (dBA)	Heating/Cooling	46 / 44	46 / 44	48 / 47	48 / 47	51 / 49	52 / 50	52 / 50
SOUND POWER LEVEL (dBA)	Cooling	65	65	67	67	69	70	70
WEIGHT (kg)		43	46	67	67	116	116	119
DIMENSIONS (mm)	Width x Depth x Height	809 x 300 + 23 x 630	809 x 300 + 23 x 630	950 x 330 + 30 x 943	950 x 330 + 30 x 943	1050 x 330 + 30 x 1338	1050 x 330 + 30 x 1338	1050 x 330 + 30 x 1338
ELECTRICAL SUPPLY		220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz
PHASE		Single	Single	Single	Single	Single	Single	Single
SYSTEM POWER	Heating/Cooling (nominal)	0.86 / 0.79	1.57 / 1.43	2.04 / 1.90	1.99 / 1.77	2.61 / 2.60	3.67 / 3.87	4.70 / 4.37
INPUT (kW)	Heating/Cooling (UK)	0.77 / 0.67	1.40 / 1.22	1.71 / 1.51	1.77 / 1.50	2.32 / 2.21	3.27 / 3.29	4.18 / 3.71
STARTING CURRENT (A)		4.0	5.0	5.0	6.0	12.0	12.0	12.0
SYSTEM RUNNING CURRENT (A)	Heating/Cooling [MAX]	4.17 / 3.82 [13.3]	7.13 / 6.49 [13.3]	9.14 / 7.98 [19.3]	8.80 / 7.81 [19.5]	11.90 / 11.87 [27.2]	16.37 / 17.30 [27.3]	21.14 / 19.75 [29.1]
FUSE RATING (BS88) - HRC (A)		16	16	25	25	32	32	40
MAINS CABLE No. Cores		3	3	3	3	3	3	3
MAX PIPE LENGTH (m)		50	50	50	50	75	75	75
MAX HEIGHT DIFFERENCE (m)		30	30	30	30	30	30	30
CHARGE R410A (kg) - 30m		2.2	2.4	3.5	3.5	5.0	5.0	5.0



Telephone: 01707 282880

email: air.conditioning@meuk.mee.com web: airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division
Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881

IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland
Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

Country of origin: United Kingdom - Japan - Thailand - Malaysia. ©Mitsubishi Electric Europe 2014. Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registered trademarks of their respective owners.



Effective as of May 2014



www.greengateway.mitsubishielectric.co.uk

Mitsubishi Electric UK's commitment to the environment

Follow us @meuk_les
Follow us @green_gateway

Connect with Green Gateway

mitsubishielectric2